

DIN Hose Fittings Swivel



20411-W
20412-W



20411-T
20412-T

公制内螺纹24°锥带O形圈 轻系列
METRIC FEMALE 24°CONE O-RING L SERIES

REF. ISO 12151-2 / DIN 20066

代 号 PART NO.		螺 纹 E	软 管 HOSE SIZE		管子外径	O形圈	尺 寸 DIMENSIONS		
编织 BRAIDED	缠绕SPIRAL	THREAD E	公称内径DN	标号 DASH	TUBE O.D.	O-RING	A	C	S2
20411-12-04WZ *	-	M12X1.5	6	04	6	O04.5X1.5	22.5	1.4	17
20411-14-04TZ *	-	M14X1.5	6	04	8	O06.5X1.5	21.5	1.4	17
20411-14-06WZ		M14X1.5	10	06	8	O06.5X1.5	23	1.6	17
20411-16-04TZ *	-	M16X1.5	6	04	10	O08.0X1.5	20.5	2.1	19
20411-16-05TZ *	-	M16X1.5	8	05	10	O08.0X1.5	23	2.1	19
20411-16-06WZ	20412-16-06WZ	M16X1.5	10	06	10	O08.0X1.5	23.5	2	19
20411-18-05TZ *	-	M18X1.5	8	05	12	O10.0X1.5	24.5	1.5	22
20411-18-06TZ *	20412-18-06TZ *	M18X1.5	10	06	12	O10.0X1.5	27.5	1.5	22
20411-18-08WZ	20412-18-08WZ	M18X1.5	12	08	12	O10.0X1.5	24.5	1.8	22
20411-22-05TZ	-	M22X1.5	8	05	15	O12.0X2.0	26.5	3	27
20411-22-06TZ	20412-22-06TZ	M22X1.5	10	06	15	O12.0X2.0	26.5	3	27
20411-22-08TZ *	20412-22-08TZ *	M22X1.5	12	08	15	O12.0X2.0	29	2.5	27
20411-26-10TZ *	20412-26-10TZ *	M26X1.5	16	10	18	O15.0X2.0	30	2.1	32
20411-26-12WZ	20412-26-12WZ	M26X1.5	20	12	18	O15.0X2.0	28.5	2.1	32
20411-30-10TZ	20412-30-10TZ	M30X2	16	10	22	O20.0X2.0	31	3.8	36
20411-30-12TZ *	20412-30-12TZ	M30X2	20	12	22	O20.0X2.0	34	4	36
20411-36-12TZ	20412-36-12TZ	M36X2	20	12	28	O26.0X2.0	33	4.5	41
20411-36-16WZ *	20412-36-16WZ	M36X2	25	16	28	O26.0X2.0	30	4.5	41
20411-45-16TZ	20412-45-16TZ	M45X2	25	16	35	O32.0X2.5	37	4	50
20411-45-20TZ *	20412N-45-20TZ	M45X2	32	20	35	O32.0X2.5	37.5/40.1	4	50
20411-52-20TZ	20412N-52-20TZ	M52X2	32	20	42	O38.0X2.5	38.5/41.1	4	60
20411-52-24TZ *	20412N-52-24TZ	M52X2	40	24	42	O38.0X2.5	38.5/41.5	4	60

1.尺寸A中"/"前尺寸适用于编织软管接头,"/"后尺寸适用于缠绕软管接头。
The dimension A before"/" is for braided hose fitting and after "/" is for spiral hose fitting.

2.代号后标有"＊"为推荐选用的规格。Part no. marked with "*" is recommended.

3. 接头及O形圈材质选项。Material options for fitting and the O-ring.

接头材质 Fitting material	O形圈材质 O-ring material	代号后缀 Part. No. suffix	代号示例 Part No. example
碳钢（默认） Carbon steel (Default)	丁腈橡胶 NBR	TZ/WZ	20411-18-06TZ
304不锈钢 304 stainless steel	氟橡胶 Viton	SRT/SRW	20411-18-06SRT
316L不锈钢 316L stainless steel	氟橡胶 Viton	SVT/SVW	20411-18-06SVT
316Ti不锈钢 316Ti stainless steel	氟橡胶 Viton	SYT/SYW	20411-18-06SYT

4.碳钢接头耐腐蚀性能选项。 Plating options and performance for carbon steel fittings.

表面处理方式 Plating method	代号后缀 Part. No. suffix	代号示例 Part No. example	耐白锈（小时） White rust (Hours)	耐红锈（小时） Red rust(Hours)
三价铬镀锌（默认）Cr3+ plating (Default)	Z	20411-18-06TZ	96	360
Durakote镀锌 Durakote plating	ZD	20411-18-06TZD	360	720
镀锌镍 Zinc-nickel plating	ZN	20411-18-06TZN	1000	-