
BSP Hose Fittings Compact Elbow



22691K
22692K

90° 英管短身内螺纹60°外锥面
90° BSP COMPACT FEMALE 60° CONE

REF. ISO 12151-6

代 号 PART NO.		螺 纹 E	软 管 HOSE SIZE		尺 寸 DIMENSIONS				
编织 BRAIDED	缠绕SPIRAL	THREAD E	公称内径 DN	标号 DASH	A	C	H	S1	S2
22691K-04-04Z	-	G1/4"X19	6	04	17.5	5.5	18.5	11	19
22691K-06-04Z	-	G3/8"X19	6	04	20	6.3	24	16	22
22691K-06-05Z	-	G3/8"X19	8	05	20	6.3	24	16	22
22691K-06-06Z	22692K-06-06Z	G3/8"X19	10	06	20	6.3	24	16	22
22691K-08-06Z	22692K-08-06Z	G1/2"X14	10	06	23	7.5	28.5	19	27
22691K-08-08Z	22692K-08-08Z	G1/2"X14	12	08	23.5	7.5	28.5	19	27
22691K-10-10Z	22692K-10-10Z	G5/8"X14	16	10	24.5	9.5	30.5	22	30
22691K-12-12Z	22692K-12-12Z	G3/4"X14	20	12	27.5	10.9	33	27	32
22691K-16-16Z	22692K-16-16Z	G1"X11	25	16	43	11.7	38.5	33	41

1.尺寸A中"/"前尺寸适用于编织软管接头,"/"后尺寸适用于缠绕软管接头。
The dimension A before"/" is for braided hose fitting and after "/" is for spiral hose fitting.

2.代号后标有"⋆ "为推荐选用的规格。Part no. marked with "⋆" is recommended.

3. 接头材质选项。Material options for fitting.

接头材质 Fitting material	代号后缀 Part. No. suffix	代号示例 Part No. example
碳钢（默认） Carbon steel (Default)	TZ/WZ	22691K-08-08Z
304不锈钢 304 stainless steel	SRT/SRW	22691K-08-08SR
316L不锈钢 316L stainless steel	SVT/SVW	22691K-08-08SV
316Ti不锈钢 316Ti stainless steel	SYT/SYW	22691K-08-08SY

4.碳钢接头耐腐蚀性能选项。 Plating options and performance for carbon steel fittings.

表面处理方式 Plating method	代号后缀 Part. No. suffix	代号示例 Part No. example	耐白锈（小时） White rust (Hours)	耐红锈（小时） Red rust(Hours)
三价铬镀锌（默认）Cr3+ plating (Default)	Z	22691K-08-08Z	96	360
Durakote镀锌 Durakote plating	ZD	22691K-08-08ZD	360	720
镀锌镍 Zinc-nickel plating	ZN	22691K-08-08ZN	1000	-